

200mA Low Consumption Linear Regulator

DESCRIPTION

BL8064 series is a group of positive voltage output, low power consumption, low dropout voltage, three terminal regulator. It can provide 200mA output current when input / output voltage differential drops to 430mV ($V_{out} = 2.8V$), The very low power consumption of BL8064 ($I_q=1.0\mu A$) can greatly improve natural life of batteries.

BL8064 can provide output value in the range of 1.1V~5.5V in 0.1V steps. It also can be customized on command.

BL8064 includes high accuracy voltage reference, error amplifier, current limit circuit and output driver module.

BL8064 has well load transient response and good temperature characteristic, And it uses trimming technique to guarantee output voltage accuracy within $\pm 2\%$.


FEATURES

- Low Power Consumption: $1.0\mu A$ (Typ.)
- Maximum Output Current: 200mA
- Small Dropout Voltage
- 210mV@100mA ($V_{out}=2.8V$)
- 430mV@200mA ($V_{out}=2.8V$)
- Input Voltage Range: 1.5V~8V
- Output Voltage Range: 1.1V~5.5V (customized on command in 0.1V steps)
- Highly Accurate: $\pm 2\%$ ($\pm 1\%$ customized)
- Output Current Limit

APPLICATIONS

- Battery Powered equipment
- Power Management of MP3、PDA、DSC、Mouse、PS2 Games
- Reference Voltage Source Regulation after Switching Power

TYPICAL APPLICATION




NOTE1: Input capacitor ($C_{in}=1\mu F$) is recommended in all application circuit. Ceramic capacitor is recommended.

NOTE2: Output capacitor ($C_{out}=1\mu F$) is recommended in all application to assure the stability of circuit. Ceramic capacitor is recommended.

ELECTRICAL CHARACTERISTICS

Output Voltage VS. Output Current ($V_{out}=2.8V$)



ORDERING INFORMATION

BL8064 1 2 3 4 5

Code	Description
1	Temperature&Rohs: C:-40~85°C ,Pb Free Rohs Std.
2	Package type: B3:SOT-23-3 B3A:TSOT-23 C3:SOT-89-3 H:TO-92
3	Packing type: TR:Tape&Reel (Standard) BG:Bag (TO-92)
4	Output voltage: e.g. 11=1.1V 15=1.5V 55=5.5V
5	Voltage accuracy: 1=±1% Blank(default)=±2%

MARKING DESCRIPTON

Output Voltage Code

VOUT	Code	VOUT	Code	VOUT	Code
1.2V	2	3.0V	0	4.4V	4
1.3V	3	3.1V	1	4.5V	5
1.5V	5	3.2V	2	4.6V	6
1.8V	8	3.3V	3	4.7V	7
2.0V	0	3.4V	4	4.8V	8
2.1V	1	3.5V	5	4.9V	9
2.2V	2	3.6V	6	5.0V	0
2.3V	3	3.7V	7	5.1V	1
2.4V	4	3.8V	8	5.2V	2
2.5V	5	3.9V	9	5.3V	3
2.6V	6	4.0V	0	5.4V	4
2.7V	7	4.1V	1	5.5V	5
2.8V	8	4.2V	2		
2.9V	9	4.3V	3		

Y: The Year of manufacturing, "9" stands for year 2009,





"0" stands for year 2010, and "1" stands for year

2011.

W: The week of manufacturing. "A" stands for week

1, "Z" stands for week 26, "A" stands for week 27, "Z" stands for week 52.

PIN CONFIGURATION

Product Classification		BL8064CB3TR□ □
Marking		SOT-23-3 
NXYW	N:Product Code	
	X:Output Voltage	
	YW: Date Code	
Product Classification		BL8064CB3ATR□ □
Marking		TSOT-23 
NXYW	N:Product Code	
	X:Output Voltage	
	YW: Date Code	
Product Classification		BL8064CC3TR□ □
Marking		SOT-89-3 
NXX LLBYW	N:Product Code	
	XX:Output Voltage	
	LL:LOT NO.	
	B:FAB Code	
	YW:Date Code	
Product Classification		BL8064CHBG□ □
Marking		TO-92 
NXX LLBYW	N:Product Code	
	XX:Output Voltage	
	LL:LOT NO.	
	B:FAB Code	
	YW:Date Code	
GND	Ground Pin	
Vin	Supply Voltage Input	
Vout	Output Voltage	

ABSOLUTE MAXIMUM RATING

Parameter		Value
Max Input Voltage		10V
Operating Junction Temperature(Tj)		125°C
Ambient Temperature(Ta)		-40°C -85°C
Power Dissipation	SOT-23-3	250mW
	TSOT-23	250mW
	SOT-89-3	500mW
	TO-92	500mW
Storage Temperature(Ts)		-40°C -150°C
Lead Temperature & Time		260°C,10S

Note:

Exceed these limits to damage to the device.

Exposure to absolute maximum rating conditions may affect device reliability.

RECOMMENDED WORK CONDITIONS


Item	Min	Recommended	Max.	Unit
Input Voltage Range			8	V
Ambient Temperature	-40		85	°C

ELECTRICAL CHARACTERISTICS

(Test Conditions: Cin=1uF, Cout=1uF, TA=25°C, Unless Otherwise Specified)

Symbol	Parameter	Conditions	Min	Type	Max	Units
Vin	Input Voltage				8	V
Vout	Output Voltage		Vout x0.98		Vout X1.02	V
Iout(Max.)	Maximum Output Current	Vin-Vout=1V	200			mA
Dropout Voltage	Input-Output Voltage Differential	Iout=100mA	Vout ≤ 1.8V	600	1000	mV
			Vout ≥ 1.8V	300	600	
$\frac{\Delta V_{out}}{\Delta V_{in} \cdot V_{out}}$	Line Regulation	Iout=10mA 1.5V≤Vin≤8V		0.2	0.3	%/V
ΔV_{out}	Load Regulation	Vin=Set Vout+1V 1mA≤Iout≤100mA		20	40	mV
Iq	Quiescent Current	Vin=Set Vout+1V		1.0	5.0	uA
$\frac{\Delta V_{out}}{\Delta T \cdot V_{out}}$	Output Voltage Temperature Coefficient	Iout=10mA		100		ppm/°C

BLOCK DIAGRAM



EXPLANATION


BL8064 is a series of low dropout voltage and low power consumption three pins regulator. Its application circuit is very simple, which only needs two outside capacitors. It is composed of these modules: high accuracy voltage reference, current limit circuit, error amplifier, output driver and power transistor.

Current Limit module can keep chip and power system away from danger when load current is more than 200mA.


BL8064 uses trimming technique to assure the accuracy of output value within $\pm 2\%$, at the same time, temperature compensation is elaborately considered in this chip, which makes BL8064's temperature coefficient within 100ppm/ $^{\circ}\text{C}$.

TYPICAL PERFORMANCE CHARACTERISTICS


1. Load regulation (Vin=4V)




2. Line regulation




3. Dropout Voltage




4. PSRR



5. Iq (Vout=2.8V)




6. Current limit




7. Line transient response

$C_{in}=C_{out}=1\mu F$ $I_{out}=10mA$ $V_{out}=2.8V$




8. Load transient response

$C_{in}=C_{out}=1\mu F$ $V_{in}=4V$ $V_{out}=2.8V$



9. Start up




PACKAGE LINE


Package	TSOT-23	Devices per reel	3000Pcs	Unit	mm
Package dimension:					
<p>Technical drawing of the TSOT-23 package. The top view shows a rectangular body with a width of 1.900 ± 0.05 mm and a total length of 2.400 ± 0.05 mm. The distance between the two leads is 1.300 ± 0.05 mm. The lead length is 0.550 ± 0.05 mm. The lead thickness is 0.400 ± 0.03 mm. The lead width is 0.400 ± 0.05 mm. The lead tip radius is $4 \times R0.1$ MAX. The side view shows a total length of 2.900 ± 0.05 mm and a height of 1.000 ± 0.05 mm. The lead height is 0.400 ± 0.05 mm. The lead tip radius is $4 \times R0.1$ MAX. The cross-sectional view shows a lead height of 0.2 MIN, a lead width of 0.100 ± 0.01 mm, and a lead thickness of 0.080 ± 0.02 mm. The lead tip radius is $4 \times R0.1$ MAX. The lead width is 0.100 ± 0.01 mm. The lead thickness is 0.080 ± 0.02 mm. The lead tip radius is $4 \times R0.1$ MAX. The lead width is 0.100 ± 0.01 mm. The lead thickness is 0.080 ± 0.02 mm. The lead tip radius is $4 \times R0.1$ MAX.</p>					

Package	SOT-23-3	Devices per reel	3000Pcs	Unit	mm
<p>Technical drawing of the SOT-23-3 package. The top view shows a rectangular body with a width of 1.9 ± 0.2 mm and a total length of 2.9 ± 0.2 mm. The distance between the two leads is 1.6 ± 0.2 mm. The lead length is 0.4 ± 0.1 mm. The lead width is 0.4 ± 0.1 mm. The lead tip radius is 3. The side view shows a total length of 2.8 ± 0.3 mm and a height of 1.6 ± 0.2 mm. The lead height is 0.4 ± 0.1 mm. The lead tip radius is 3. The cross-sectional view shows a lead height of 0.2 MIN, a lead width of 0.16 ± 0.1 mm, and a lead thickness of 0.2 MIN. The lead tip radius is 3. The lead width is 0.16 ± 0.1 mm. The lead thickness is 0.2 MIN. The lead tip radius is 3.</p>					

BL8064

Package	SOT-89-3	Devices per reel	1000Pcs	Unit	mm
Package Dimension:					
 <p>The technical drawing illustrates the BL8064 package in three views: top, side, and bottom. The top view shows a rectangular package with a width of 4.5 ± 0.1 mm and a central circular feature with a diameter of $\varnothing 1.0$ mm. A trapezoidal feature is located at the top, with a width of 1.6 ± 0.2 mm and a height of 0.4 mm. The package has three leads labeled 1, 2, and 3, with a minimum height of 0.8 mm. The side view shows a height of 2.5 ± 0.1 mm and a maximum height of 4.25 mm. The bottom view shows a trapezoidal shape with a width of 1.5 ± 0.1 mm and a height of 0.47 ± 0.1 mm. The distance from the center to the edges is 0.42 ± 0.2 mm.</p>					

BL8064

Package	TO-92	Devices per Bag	1000Pcs	Unit	mm
Package Dimension:					
TO-92					
 <p>The technical drawing illustrates the dimensions of a TO-92 package. The top view shows a semi-circular body with a diameter of $\Phi 1.5 \times 0.2$ mm. The total height is 3.5 ± 0.1 mm, and the height from the base to the top of the body is 1.25 ± 0.1 mm. The width of the top section is 2.54 mm, and the lead angle is 5°. The side view shows a total height of 4.95 ± 0.35 mm and a diameter of $\Phi 4.5 \pm 0.1$ mm. The lead length is 14.3 ± 0.1 mm, with a lead diameter of 0.38 mm. The distance from the base to the start of the lead is 0.46 mm, and the distance from the base to the end of the lead is 1.5 mm. The distance between the leads is 0.5 mm.</p>					