


**U74AUP1G06****CMOS IC****LOW-POWER SINGLE
INVERTER BUFFER/DRIVER
WITH OPEN-DRAIN OUTPUTS****DESCRIPTION**

The **U74AUP1G06** is a single inverting buffer with open-drain outputs and it provides the function $Y = \overline{A}$ in positive logic. The output of this device is open-drain, and can be connected to other open-drain outputs to implement active-low wired-OR or active-high wired-AND functions.

This device ensures a very low static and dynamic power consumption across the entire V_{CC} range from 0.8V to 3.6V.

This device has power-down protective circuit, preventing device destruction when it is powered down.

**FEATURES**

- * Wide supply voltage range from 0.8V to 3.6V
- * Inputs accept voltages up to 3.6V
- * I_{OFF} supports partial-power-down mode
- * Low static power consumption; $I_{CC} = 0.5\mu A$ (Max.)
- * Optimized for 3.3V Operation

ORDERING INFORMATION



Ordering Number	Package	Packing
U74AUP1G06G-AE5-R	SOT-23-5	Tape Reel
U74AUP1G06G-AL5-R	SOT-353	Tape Reel
U74AUP1G06G-K06-1010-R	DFN-6(1.0×1.0)	Tape Reel

U74AUP1G06G-AE5-R (1) Packing Type (2) Package Type (3) Green Package	(1) R: Tape Reel (2) AE5: SOT-23-5, AL5: SOT-353, K06-1010: DFN-6(1.0×1.0) (3) G: Halogen Free and Lead Free
--	---

MARKING

SOT-23-5 / SOT-353	DFN-6(1.0×1.0)

PIN CONFIGURATION





FUNCTION TABLE

INPUT(A)	OUTPUT(Y)
H	L
L	Z

Note: H: HIGH voltage level; L: LOW voltage level; Z: high impedance state.

LOGIC DIAGRAM (positive logic)



■ ABSOLUTE MAXIMUM RATING

PARAMETER	SYMBOL	TEST CONDITIONS	RATINGS	UNIT
Supply Voltage	V_{CC}		-0.5 ~ +4.6	V
Input Voltage	V_{IN}		-0.5 ~ +4.6	V
Output Voltage	V_{OUT}	Output in the high or low state	-0.5 ~ $V_{CC} + 0.5$	V
		Output in the power-off state	-0.5 ~ +4.6	V
Continuous V_{CC} or GND Current	I_{CC}		±50	mA
Continuous Output Current	I_{OUT}	$V_{OUT}=0 \sim V_{CC}$	±20	mA
Input Clamp Current	I_{IK}	$V_{IN} < 0$	-50	mA
Output Clamp Current	I_{OK}	$V_{OUT} > V_{CC}$ or $V_{OUT} < 0$	-50	mA
Storage Temperature Range	T_{STG}		-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}	Operating	0.8		3.6	V
Input Voltage	V_{IN}		0		3.6	V
Output Voltage	V_{OUT}	High or low state	0		V_{CC}	V
Operating Temperature	T_A		-40		85	°C
Input Transition Rise or Fall Rate	$\Delta t/\Delta v$	$V_{CC}=0.8V \sim 3.6V$			200	ns/V

■ ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
High-level Input Voltage	V_{IH}	$V_{CC}=0.8V$	V_{CC}			V
		$V_{CC}=1.1V \sim 1.95V$	$0.65 \times V_{CC}$			V
		$V_{CC}=2.3V \sim 2.7V$	1.6			V
		$V_{CC}=3.0V \sim 3.6V$	2			V
Low-level Input Voltage	V_{IL}	$V_{CC}=0.8V$			0	V
		$V_{CC}=1.1V \sim 1.95V$			$0.35 \times V_{CC}$	V
		$V_{CC}=2.3V \sim 2.7V$			0.7	V
		$V_{CC}=3.0V \sim 3.6V$			0.9	V
Low-Level Output Voltage	V_{OL}	$V_{CC}=0.8V \sim 3.6V$, $I_{OL}=20\mu A$			0.1	V
		$V_{CC}=1.1V$, $I_{OL}=1.1mA$			$0.3 \times V_{CC}$	V
		$V_{CC}=1.4V$, $I_{OL}=1.7mA$			0.31	V
		$V_{CC}=1.65V$, $I_{OL}=1.9mA$			0.31	V
		$V_{CC}=2.3V$	$I_{OL}=2.3mA$		0.31	V
			$I_{OL}=3.1mA$		0.44	v
		$V_{CC}=3.0V$	$I_{OL}=2.7mA$		0.31	V
			$I_{OL}=4.0mA$		0.44	v
Input Leakage Current	$I_{I(LEAK)}$	$V_{CC}=0V \sim 3.6V$, $V_{IN}=GND \sim 3.6$			±0.1	μA
Power OFF Leakage Current	I_{off}	$V_{CC}=0V$, V_{IN} or $V_{OUT}=0V \sim 3.6V$			±0.2	μA
Additional Power OFF Leakage Current	ΔI_{off}	$V_{CC}=0V \sim 0.2V$, V_{IN} or $V_{OUT}=0V \sim 3.6V$			±0.2	μA
Quiescent Supply Current	I_{CC}	$V_{CC}=0.8V \sim 3.6V$, $I_{OUT}=0$ $V_{IN}=GND$ or $V_{CC} \sim 3.6V$			0.5	μA
Additional Quiescent Supply Current Per Input Pin	ΔI_{CC}	$V_{CC}=3.3V$, $V_{IN}=V_{CC}-0.6V$, $I_{OUT}=0$			40	μA
Input Capacitance	C_I	$V_{CC}=0V$, $V_{IN}=V_{CC}$ or GND		1.5		pF
		$V_{CC}=3.6V$, $V_{IN}=V_{CC}$ or GND		1.7		pF
Output Capacitance	C_{OUT}	$V_{CC}=0V$, $V_{OUT}=GND$		1.7		pF

■ SWITCHING CHARACTERISTICS ($T_A = 25^\circ\text{C}$, Input: $t_R / t_F = 3\text{ns}$, unless otherwise specified)


See Fig. 1 and Fig. 2 for test circuit and waveforms.

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation delay from input (A) to output(Y)	t_{PD}	$C_L = 5\text{pF}$, $R_L = 5\text{k}\Omega$	$V_{CC} = 0.8\text{V}$	12.8		ns
			$V_{CC} = 1.1\text{V} \pm 0.1\text{V}$	2.3	12	ns
			$V_{CC} = 1.5\text{V} \pm 0.1\text{V}$	1.8	3.5	ns
			$V_{CC} = 1.8\text{V} \pm 0.15\text{V}$	1.5	3.1	ns
			$V_{CC} = 2.5\text{V} \pm 0.2\text{V}$	1.2	2.2	ns
			$V_{CC} = 3.3\text{V} \pm 0.3\text{V}$	1.1	2.2	ns
		$C_L = 10\text{pF}$, $R_L = 5\text{k}\Omega$	$V_{CC} = 0.8\text{V}$	15.8		ns
			$V_{CC} = 1.1\text{V} \pm 0.1\text{V}$	2.7	12	ns
			$V_{CC} = 1.5\text{V} \pm 0.1\text{V}$	2.2	4.3	ns
			$V_{CC} = 1.8\text{V} \pm 0.15\text{V}$	1.9	3.9	ns
			$V_{CC} = 2.5\text{V} \pm 0.2\text{V}$	1.9	2.9	ns
			$V_{CC} = 3.3\text{V} \pm 0.3\text{V}$	1.6	3.0	ns
		$C_L = 15\text{pF}$, $R_L = 5\text{k}\Omega$	$V_{CC} = 0.8\text{V}$	18.8		ns
			$V_{CC} = 1.1\text{V} \pm 0.1\text{V}$	3.2	12	ns
			$V_{CC} = 1.5\text{V} \pm 0.1\text{V}$	2.6	5.0	ns
			$V_{CC} = 1.8\text{V} \pm 0.15\text{V}$	2.3	4.8	ns
			$V_{CC} = 2.5\text{V} \pm 0.2\text{V}$	2.1	3.5	ns
			$V_{CC} = 3.3\text{V} \pm 0.3\text{V}$	2.0	3.8	ns
		$C_L = 30\text{pF}$, $R_L = 5\text{k}\Omega$	$V_{CC} = 0.8\text{V}$	27.8		ns
			$V_{CC} = 1.1\text{V} \pm 0.1\text{V}$	4.4	12	ns
			$V_{CC} = 1.5\text{V} \pm 0.1\text{V}$	3.6	7.6	ns
			$V_{CC} = 1.8\text{V} \pm 0.15\text{V}$	3.2	7.4	ns
			$V_{CC} = 2.5\text{V} \pm 0.2\text{V}$	2.9	5.4	ns
			$V_{CC} = 3.3\text{V} \pm 0.3\text{V}$	2.9	6.5	ns

■ OPERATING CHARACTERISTICS ($f = 10\text{MHz}$, $T_A = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Power Dissipation Capacitance	C_{PD}	$V_{CC} = 0.8\text{V}$		1.0		pF
		$V_{CC} = 1.1\text{V} \pm 0.1\text{V}$		1.0		pF
		$V_{CC} = 1.5\text{V} \pm 0.1\text{V}$		1.0		pF
		$V_{CC} = 1.8\text{V} \pm 0.15\text{V}$		1.0		pF
		$V_{CC} = 2.5\text{V} \pm 0.2\text{V}$		1.0		pF
		$V_{CC} = 3.3\text{V} \pm 0.3\text{V}$		1.0		pF

■ TEST CIRCUIT AND WAVEFORMS



Note:1. Since this device has open drain outputs, the t_{PLZ} and t_{PZL} is the same as t_{PLH} and t_{PHL} .

Fig. 1 LOAD CIRCUITRY FOR SWITCHING TIMES

V_{CC}	V_{IN}	t_R / t_F	V_M	V_{LOAD}	C_L	R_L	V_{Δ}
0.8	V_{CC}	3ns	$V_{CC}/2$	$2 \times V_{CC}$	5,10,15,30pF	5k Ω	0.1V
$1.2 \pm 0.1V$	V_{CC}	3ns	$V_{CC}/2$	$2 \times V_{CC}$	5,10,15,30pF	5k Ω	0.1V
$1.5 \pm 0.1V$	V_{CC}	3ns	$V_{CC}/2$	$2 \times V_{CC}$	5,10,15,30pF	5k Ω	0.1V
$1.8 \pm 0.15V$	V_{CC}	3ns	$V_{CC}/2$	$2 \times V_{CC}$	5,10,15,30pF	5k Ω	0.15V
$2.5 \pm 0.2V$	V_{CC}	3ns	$V_{CC}/2$	$2 \times V_{CC}$	5,10,15,30pF	5k Ω	0.15V
$3.3 \pm 0.3V$	V_{CC}	3ns	$V_{CC}/2$	$2 \times V_{CC}$	5,10,15,30pF	5k Ω	0.3V




Fig. 2 PROPAGATION DELAY FROM INPUT(A) TO OUTPUT(Y) AND OUTPUT TRANSITION TIME

Notes: 1. C_L includes probe and jig capacitance.

2. All input pulses are supplied by generators having the following characteristics: PRR $\leq 10\text{MHz}$, $Z_O = 50\Omega$.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.