



TIP36C



PNP SILICON TRANSISTOR

HIGH POWER TRANSISTORS

DESCRIPTION

The UTC **TIP36C** is a PNP Expitaxial-Base transistor, designed for using in general purpose amplifier and switching applications. Complement to TIP35C.

INTERNAL SCHEMATIC DIAGRAM



ORDERING INFORMATION

Order Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
TIP36CL-x-T3P-T	TIP3CG-x-T3P-T	TO-3P	B	C	E	Tube
TIP36CL-x-T3N-T	TIP3CG-x-T3N-T	TO-3PN	B	C	E	Tube

<p>TIP36CL-x-T3P-T</p> <ul style="list-style-type: none"> (1) Packing Type (2) Package Type (3) Rank (4) Lead Plating 	<ul style="list-style-type: none"> (1) T: Tube (2) T3P: TO-3P, T3N: TO-3PN (3) refer to Classification of h_{FE1} (4) L: Lead Free, G: Halogen Free
---	--

■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage ($I_E = 0$)	V_{CBO}	-100	V
Collector-Emitter Voltage ($I_B = 0$)	V_{CEO}	-100	V
Emitter-Base Voltage ($I_C = 0$)	V_{EBO}	-5	V
Collector Current	I_C	-25	A
Collector Peak Current	I_{CM}	-50	A
Base Current	I_B	-5	A
Total Dissipation ($T_C = 25^\circ\text{C}$)	P_D	125	W
Junction Temperature	T_J	+150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-65 ~ +150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Thermal Resistance Junction-Case	θ_{JC}			1	$^\circ\text{C/W}$






■ ELECTRICAL CHARACTERISTICS ($T_C = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector Cut-off Current ($I_E = 0$)	I_{CBO}	$V_{CB} = -100\text{ V}$			-10	μA
Emitter Cut-off Current ($I_C = 0$)	I_{EBO}	$V_{EB} = -5\text{ V}$			-10	μA
Collector-Emitter Sustaining Voltage ($I_B = 0$)	$V_{(BR)CEO}$	$I_C = -50\text{ mA}$	-100			V
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_B = -1.5\text{ A}, I_C = -15\text{ A}$			-1.8	V
		$I_B = -5\text{ A}, I_C = -25\text{ A}$			-4	V
Base-Emitter Voltage	$V_{BE(ON)}$	$V_{CE} = -5\text{ V}, I_C = -5\text{ A}$			-1.5	V
DC Current Gain	h_{FE1}	$V_{CE} = -5\text{ V}, I_C = -1.5\text{ A}$	55		160	
	h_{FE2}	$V_{CE} = -4\text{ V}, I_C = -15\text{ A}$	15			
Transition Frequency	f_T	$V_{CE} = -5\text{ V}, I_C = -1\text{ A}$	3			MHz

■ CLASSIFICATION OF h_{FE1}

RANK	R	O
RANGE	55~110	80~160

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.