



**DTA144E****PNP SILICON TRANSISTOR****DIGITAL TRANSISTORS  
(BUILT-IN BIAS RESISTORS)****■ FEATURES**


- \* Built-in bias resistors that implies easy ON/OFF applications.
- \* The bias resistors are thin-film resistors with complete isolation to allow positive input.

**■ EQUIVALENT CIRCUIT****■ ORDERING INFORMATION**

Ordering Number	Package	Pin Assignment			Packing
		1	2	3	
DTA144EG-AE3-R	SOT-23	G	I	O	Tape Reel
DTA144EG-AL3-R	SOT-323	G	I	O	Tape Reel
DTA144EG-AN3-R	SOT-523	G	I	O	Tape Reel

Note: Pin Assignment: G: GND I: IN O: OUT

DTA144EG-AE3-R	(1)Packing Type (2)Package Type (3)Green Package	(1) B: Tape Box, K: Bulk, R: Tape Reel (2) AE3: SOT-23, AL3: SOT-323, AN3: SOT-523 (3) G: Halogen Free and Lead Free, L: Lead Free
----------------	--	--

**■ MARKING**

■ ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ , unless otherwise specified)

PARAMETER		SYMBOL	RATING	UNIT
Supply Voltage		$V_{CC}$	-50	V
Input Voltage		$V_{IN}$	-40~+10	V
Output Current		$I_{OUT}$	-30	mA
		$I_{O(MAX)}$	-100	
Power Dissipation	SOT-523	$P_D$	150	mW
	SOT-23/SOT-323		200	mW
Junction Temperature		$T_J$	150	$^\circ\text{C}$
Storage Temperature		$T_{STG}$	-55~+150	$^\circ\text{C}$

Note Absolute maximum ratings are those values beyond which the device could be permanently damaged.





Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input Voltage	$V_{IN(OFF)}$	$V_{CC} = -5\text{V}$ , $I_{OUT} = -100\mu\text{A}$			-0.5	V
	$V_{IN(ON)}$	$V_{OUT} = -0.3\text{V}$ , $I_{OUT} = -2\text{mA}$	-3			V
Output Voltage	$V_{OUT(ON)}$	$I_{OUT}/I_{IN} = -10\text{mA}/-0.5\text{ mA}$		-0.1	-0.3	V
Input Current	$I_{IN}$	$V_{IN} = -5\text{V}$			-0.18	mA
Output Current	$I_{OUT(OFF)}$	$V_{CC} = -50\text{V}$ , $V_{IN} = 0\text{V}$			-0.5	$\mu\text{A}$
DC Current Gain	$h_{FE}$	$V_{OUT} = -5\text{V}$ , $I_{OUT} = -5\text{mA}$	68			
Input Resistance	$R_1$		32.9	47	61.1	k $\Omega$
Resistance Ratio	$R_2/R_1$		0.8	1	1.2	
Transition Frequency	$f_T$	$V_{CE} = -10\text{ V}$ , $I_E = 5\text{mA}$ , $f = 100\text{MHz}$ (Note)		250		MHz

Note: Transition frequency of the device.

## ■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.