

UT2352



Power MOSFET

-30V, -1.3A P-CHANNEL ENHANCEMENT MODE

■ DESCRIPTION

As P-Channel Logic Level MOSFET, **UT2352** has been optimized for battery power management applications. And it's produced using UTC's advanced Power Trench process.

■ SYMBOL



■ ORDERING INFORMATION

| Ordering Number | Package | Pin Assignment | | | | | | | | acking |
|--------------------|------------|----------------|---|---|---|---|---|---|---|-----------|
| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | |
| UT2352G-AE3-R | SOT-23 | S | G | D | - | - | - | - | - | Tape Reel |
| UT2352G-K08-3030-R | DFN-8(3x3) | S | S | S | G | D | D | D | D | Tape Reel |

Note: Pin Assignment: G: Gate D: Drain S: Source

| | | |
|-------------------|--|--|
| UT2352G-AE3-R | (1)Packing Type (2)Package Type (3)Green Package | (1) R: Tape Reel (2) AE3: SOT-23, K08-3030: DFN-8(3x3) (3) G: Halogen Free and Lead Free |
|-------------------|--|--|

■ MARKING

| SOT-23 | DFN-8(3x3) |
|----------|----------------------------------|
| BCBG | UT 2352 • Date Code |

■ ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$, unless otherwise specified)

| PARAMETER | SYMBOL | RATING | UNIT |
|----------------------------|------------|------------|------------------|
| Drain-Source Voltage | V_{DSS} | -30 | V |
| Gate-Source Voltage | V_{GSS} | ± 25 | V |
| Continuous Drain Current | I_D | -1.3 | A |
| Pulsed Drain Current | I_{DM} | -10 | A |
| Power Dissipation (Note 3) | SOT-23 | 0.46 | W |
| | DFN-8(3x3) | 2.4 | W |
| Junction Temperature | T_J | +150 | $^\circ\text{C}$ |
| Storage Temperature | T_{STG} | -55 ~ +150 | $^\circ\text{C}$ |

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL RESISTANCES CHARACTERISTICS

| PARAMETER | SYMBOL | RATING | UNIT |
|------------------------------|------------|--------|---------------------------|
| Junction-to-Ambient (Note 3) | SOT-23 | 250 | $^\circ\text{C}/\text{W}$ |
| | DFN-8(3x3) | 52 | $^\circ\text{C}/\text{W}$ |
| Junction-to-Case | SOT-23 | 75 | $^\circ\text{C}/\text{W}$ |
| | DFN-8(3x3) | 3 | $^\circ\text{C}/\text{W}$ |

■ ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, unless otherwise specified)



| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--|------------------------------|--|------|------|-----------|----------------------------|
| OFF CHARACTERISTICS | | | | | | |
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0\text{V}$, $I_D=-250\mu\text{A}$ | -30 | | | V |
| Drain-Source Leakage Current | I_{DSS} | $V_{DS}=-24\text{V}$, $V_{GS}=0\text{V}$ | | | -1 | μA |
| Gate-Source Leakage Current | I_{GSS} | $V_{GS}=\pm 25\text{V}$, $V_{DS}=0\text{V}$ | | | ± 100 | nA |
| Breakdown Voltage Temperature Coefficient | $\Delta BV_{DSS}/\Delta T_J$ | Reference to 25°C , $I_D=-250\mu\text{A}$ | | -17 | | $\text{mV}/^\circ\text{C}$ |
| ON CHARACTERISTICS | | | | | | |
| Gate Threshold Voltage | $V_{GS(\text{TH})}$ | $V_{DS}=V_{GS}$, $I_D=-250\mu\text{A}$ | -0.8 | -2.0 | -2.5 | V |
| Drain-Source On-State Resistance (Note 2) | $R_{DS(\text{ON})}$ | $V_{GS}=-10\text{V}$, $I_D=-1.3\text{A}$ | | 150 | 180 | $\text{m}\Omega$ |
| | | $V_{GS}=-4.5\text{V}$, $I_D=-1.1\text{A}$ | | 250 | 300 | $\text{m}\Omega$ |
| DYNAMIC CHARACTERISTICS | | | | | | |
| Input Capacitance | C_{ISS} | $V_{GS}=0\text{V}$, $V_{DS}=-15\text{V}$, $f=1\text{MHz}$ | | 150 | | pF |
| Output Capacitance | C_{OSS} | | | 40 | | pF |
| Reverse Transfer Capacitance | C_{RSS} | | | 20 | | pF |
| SWITCHING CHARACTERISTICS | | | | | | |
| Total Gate Charge | Q_G | $V_{DS}=-10\text{V}$, $V_{GS}=-4.5\text{V}$, $I_D=-0.9\text{A}$ | | 1.4 | 1.9 | nC |
| Gate-Source Charge | Q_{GS} | | | 0.5 | | nC |
| Gate-Drain Charge | Q_{GD} | | | 0.5 | | nC |
| Turn-ON Delay Time (Note 2) | $t_{D(\text{ON})}$ | $V_{DD}=-10\text{V}$, $V_{GS}=-10\text{V}$, $I_D=-1\text{A}$, $R_G=6\Omega$ | | 4 | 8 | ns |
| Turn-ON Rise Time | t_R | | | 15 | 28 | ns |
| Turn-OFF Delay Time | $t_{D(\text{OFF})}$ | | | 10 | 18 | ns |
| Turn-OFF Fall Time | t_F | | | 1 | 2 | ns |
| SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS | | | | | | |
| Drain-Source Diode Forward Voltage (Note 2) | V_{SD} | $V_{GS}=0\text{V}$, $I_S=-0.42\text{ A}$ | | -0.8 | -1.2 | V |
| Maximum Continuous Drain Source Diode Forward Current | I_S | | | | -0.42 | A |
| Reverse Recovery Time | t_{RR} | $I_F = -3.9\text{ A}$, $dI_F/dt = 100\text{ A}/\mu\text{s}$ | | 17 | | ns |
| Reverse Recovery Charge | Q_{RR} | | | 7 | | nC |

Notes: 1. Pulse width limited by $T_{J(\text{MAX})}$






2. Pulse width $\leq 300\text{us}$, duty cycle $\leq 2\%$.

3. Surface mounted on 0.001 in² pad of 2oz. copper; $270^\circ\text{C}/\text{W}$ when mounted on min.

■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.

