



UT4422

Power MOSFET

N-CHANNEL ENHANCEMENT MODE FIELD EFFECT TRANSISTOR



DESCRIPTION

The **UT4422** uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with low gate voltages. This device is suitable for use as a load switch or in PWM applications.

FEATURES

- * $R_{DS(ON)} < 15\text{ m}\Omega @ V_{GS} = 10\text{V}, I_D = 11\text{A}$
- * $R_{DS(ON)} < 24\text{ m}\Omega @ V_{GS} = 4.5\text{V}, I_D = 10\text{A}$
- * Low Capacitance
- * Low Gate Charge
- * Fast Switching Capability
- * Avalanche Energy Specified

SYMBOL




ORDERING INFORMATION

Ordering Number	Package	Pin Assignment								Packing
		1	2	3	4	5	6	7	8	
UT4422G-S08-R	SOP-8	S	S	S	G	D	D	D	D	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>UT4422G-S08-R</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Green Package</p>	<p>(1) R: Tape Reel</p> <p>(2) S08: SOP-8</p> <p>(3) G: Halogen Free and Lead Free</p>
---	--

MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V_{DSS}	30	V
Gate-Source Voltage	V_{GSS}	± 20	V
Continuous Drain Current ($T_A=25^\circ\text{C}$) (Note 1)	I_D	11	A
Pulsed Drain Current	I_{DM}	50	A
Power Dissipation ($T_C=25^\circ\text{C}$)	P_D	3	W
Junction Temperature	T_J	+150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Pulse width limited by $T_{J(MAX)}$







■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	59 ~ 75	$^\circ\text{C/W}$
Junction to Case	θ_{JC}	16 ~ 24	$^\circ\text{C/W}$






■ ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS} = 0\text{ V}, I_D = 250\ \mu\text{A}$	30			V
Drain-Source Leakage Current	I_{DSS}	$V_{DS} = 24\text{ V}, V_{GS} = 0\text{ V}$		0.003	1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{DS} = 0\text{ V}, V_{GS} = \pm 20\text{ V}$			100	nA
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$	1	1.8	3	V
On State Drain Current	$I_{D(ON)}$	$V_{DS} = 5\text{ V}, V_{GS} = 4.5\text{ V}$	40			A
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS} = 10\text{ V}, I_D = 11\text{ A}$		12.6	15	m Ω
		$V_{GS} = 4.5\text{ V}, I_D = 10\text{ A}$		19.6	24	m Ω
DYNAMIC PARAMETERS						
Input Capacitance	C_{ISS}	$V_{DS} = 15\text{ V}, V_{GS} = 0\text{ V}, f = 1\text{ MHz}$	800	1040	1250	pF
Output Capacitance	C_{OSS}		140	180	220	pF
Reverse Transfer Capacitance	C_{RSS}		80	110	140	pF
SWITCHING PARAMETERS						
Total Gate Charge	Q_G	$V_{DS} = 15\text{ V}, V_{GS} = 10\text{ V}, I_D = 11\text{ A}$	15	19.8	24	nC
Gate Source Charge	Q_{GS}		2.5			nC
Gate Drain Charge	Q_{GD}		3.5			nC
Turn-ON Delay Time	$t_{D(ON)}$	$V_{GS} = 10\text{ V}, V_{DS} = 15\text{ V}, R_L = 1.35\ \Omega, R_{GEN} = 3\ \Omega$		4.5	6.5	ns
Turn-ON Rise Time	t_R		3.9	5.5	ns	
Turn-OFF Delay Time	$t_{D(OFF)}$		17.4	25	ns	
Turn-OFF Fall-Time	t_F		3.2	5	ns	
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Diode Forward Voltage	V_{SD}	$I_S = 1\text{ A}, V_{GS} = 0\text{ V}$		0.75	1	V
Maximum Body-Diode Continuous Current	I_S				4.3	A
Body Diode Reverse Recovery Time	t_{RR}	$I_F = 11\text{ A}, dI/dt = 100\text{ A}/\mu\text{s}$		17.5	21	ns
Body Diode Reverse Recovery Charge	Q_{RR}		9.3	12	nC	

TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.